

# QFCT-1000MD

Fixed Wireless Phone supports

*GSM / PSTN dual operation mode Fixed Wireless Phone with friendly user interface, large capability phone book and message storage.*



## Outstanding Features

- GSM / PSTN dual operation modes
- Support AMR Function
- Remote management through SMS
- Multi-language support, English, Turkish, Spanish etc
- Phone book : Up to 200 records
- Adjustable volume while talking
- Big Dot-matrix 128 x 64 LCD, backlight
- Redial and hand free dial numbers function
- One key dialing and incoming call blacklist
- Displaying battery level and Rx signal strength
- Services including CLIP, Call Waiting / Call Hold, Call Transferring, Call Barring etc.
- Locked to specified operator, Cell lock (up to 9 cells), Interlock of phone and SIM card
- Low voltage shockproof protection technique with Low battery / Battery Full indication voice

Specification	
<ul style="list-style-type: none"><li>✦ <b>PSTN</b></li><li>✦ <b>Air Interface Standard</b><ul style="list-style-type: none"><li>• GSM Phase 2+</li></ul></li><li>✦ <b>Phase Error</b><ul style="list-style-type: none"><li>• &lt;5°RMS</li></ul></li><li>✦ <b>Frequency Stability</b><ul style="list-style-type: none"><li>• Superior to 2.5PPM</li></ul></li><li>✦ <b>Compliant to GSM phase 2/2+</b><ul style="list-style-type: none"><li>• Class 4 (2 W @ 850/900 MHz)</li><li>• Class 1 (1 W @ 1800/1900 MHz)</li></ul></li><li>✦ <b>Environment</b><ul style="list-style-type: none"><li>• Operating temperature range: -20°C to +55°C</li><li>• Storage temperature range: -40°C to + 85°C</li><li>• Humidity: 5% to 95%</li><li>• Atmospheric Pressure: 86kPa~106kPa</li><li>• Ambient Noise: ≤ 60dB (A)</li></ul></li><li>✦ <b>Connectors</b><ul style="list-style-type: none"><li>• One USB (Type B)</li><li>• DC power input jack</li><li>• OneRJ11(6P6C)</li></ul></li></ul>	<ul style="list-style-type: none"><li>✦ <b>Antenna</b><ul style="list-style-type: none"><li>• Built-in short antenna</li><li>• Gain 1.2~1.5 dBi</li><li>• Higher gain outdoor antennas available (optional)</li></ul></li><li>✦ <b>Operating Voltage</b><ul style="list-style-type: none"><li>• DC 4.6V 1A</li></ul></li><li>✦ <b>Power Supply</b><ul style="list-style-type: none"><li>• Power Supply: 100~240V AC</li><li>• Power Consumption: ≤2W</li></ul></li><li>✦ <b>Battery Backup (optional)</b><ul style="list-style-type: none"><li>• In-built Re-chargeable NI-MH battery, 800mA(3 cell)</li><li>• Up to 4-6 hours of talking time or 100 hours of standby</li></ul></li><li>✦ <b>Sensitivity</b><ul style="list-style-type: none"><li>• Receiving Sensitivity: -104dbm</li></ul></li><li>✦ <b>Giftbox Dimension</b><ul style="list-style-type: none"><li>• 297x232x80mm</li></ul></li><li>✦ <b>Carton Measurement</b><ul style="list-style-type: none"><li>• 608x425x258mm</li><li>• 10 Pcs / Carton</li></ul></li><li>✦ <b>Gross Weight</b><ul style="list-style-type: none"><li>• 1.05kg</li></ul></li></ul>

\* Features are subject to change without notice

© Copyright 2008, QiiQ Communications Inc. All Rights Reserved. Features and specifications subject to change without notice.



327 Renfrew Drive, Unit 202, Markham, Ontario, Canada L3R 9S8  
Tel: +1-905-948-1475 Fax: +1-905-948-1655  
URL: <http://www.qiiq.com> eMail: [info@qiiq.com](mailto:info@qiiq.com)