

QG1000L

GSM Fixed Wireless Phone (without SMS)



Unique Functions

- GSM Quad-band 850/900/1800/1900
- Keypad and LCD backlight in blue
- Easy to use.
- Multi-language support, English, Chinese and Spanish
- Locked to specified operator, Cell lock (up to 9 cells), Interlock of phone and SIM card

Features

- Low voltage shockproof protection technique with Low battery / Battery Full indication voice
- Support with supplementary services including CLIP, Call Waiting / Call Hold, Call Transferring, Call Barring
- Polyphonic ring tone
- Inquiry 10 Incoming / Outgoing / Missed calls
- Automatically add local area code and pre-defined prefix IP number
- Standby time: 50 hours
- Accurate clock inside
- Displaying battery level and Rx signal strength
- Quickly response on pressing the keys

Technical Specifications

- Air Interface Standard
 - GSM Phase 2+
- Phase Error
 - 5°RMS
- Frequency Stability
 - Superior to 2.5PPM
- Compliant to GSM phase 2/2+
 - Class 4 (2 W @ 850/900 MHz)
 - Class 1 (1 W @ 1800/1900 MHz)
- Environment
 - Operating temperature range: -10°C to +50°C
 - Storage temperature range: -40°C to +60°C
 - Humidity: 5% to 95%
 - Atmospheric Pressure: 86kPa~106kPa
 - Ambient Noise: ≤ 60 dB (A)
- Sensitivity
 - Receiving Sensitivity: -104dbm
- Connectors
 - Antenna connector
 - DC power input jack
- Antenna
 - Dipole antenna
 - Gain in 2 dBi
- Higher gain outdoor antennas available (optional)
- Operating Voltage
 - 4.6V DC
- Power Supply
 - Power Supply: 220V AC
 - Power Consumption: 0.2W
- Battery Backup (optional)
 - In-built Re-chargeable NI-MH battery, 800mA
 - Up to 4-6 hours of air time or 50 hours of standby
- Giftbox dimension
 - 279*232*70 mm
- Carton measurement
 - 575*375*258 mm
 - 10 Pcs / Carton
- Weight
 - 1.01 kg



© Copyright 2007, QiiQ Communications Inc. All Rights Reserved. Features and specifications subject to change without notice.